



Wall Split

Residential series

MODEL			UNO12IV-WIFI	UNO18IV-WIFI	
Nameplate Parameter	Rated Capacity	Cooling	12351(3412~13034)	18000(5121~18500)	
		Heating	12556(3480~13580)	18493(5150~18900)	
	Rated Power Consumption	Cooling	1150(300~1600)	1675(476~2220)	
		Heating	1050(300~1600)	1688(470~1726)	
	Rated Running Current	Cooling	5.2(1.4~7.3)	7.61(2.17~10.10)	
		Heating	4.8(1.4~7.3)	7.67(2.14~7.84)	
	Max. Input Power	Cooling	1600	2220	
		Heating	1600	1726	
	Max. Input Current	Cooling	7.3	10.1	
		Heating	7.3	7.84	
	EER Cooling	W/W	3.21	3.15	
	COP Heating	W/W	3.32	3.21	
	Power supply source	V/Ph/Hz	220-240V/50HZ	220-240V/50HZ	
	Refrigerant		R410A	R410A	
	Refrigerant Charged	g	750	820	
	Max. Discharge Pressure	Mpa	4.15	4.15	
	Max. Suction Pressure	Mpa	1.15	1.15	
	Air Flow Volume	m ³ /h	680	800	
Noise level	dB(A)	35	39		
Noise level	dB(A)	45	51		
Indoor unit (Net/Gross weight)	Kg	10/12	12/14		
Outdoor unit (Net/Gross weight)	Kg	24/27(with pipe)	29/32(with pipe)		
Others	Packing Type(6 face/4 face)		6	6	
	Dimension	Net Dimension (WidthxDepthxHeight)	mm	800*190*292	850*190*292
		Packing Dimension (WidthxDepthxHeight)	mm	860*330*270	905*340*270
		Connect pipe	Liquid tube Diameter	mm	Φ6
	Compressor Parameter	Gas tube Diameter	mm	Φ9.52	Φ12
		Compressor Brand		GMCC	GMCC
	Dimension	Type		ROTARY	ROTARY
		Net Dimension (WidthxDepthxHeight)	mm	743*250*436	795*266*565
		Packing Dimension (WidthxDepthxHeight)	mm	796*338*485	855*355*610
	Loading Qty (20/40Q/40HQ)	Set	126/270/350	76/208/263	

INVERTER

Outdoor Unit



Features



Timer



Auto Mode



Auto Swing



Super Turbo



Dry Mode



Refrigerant Leakage Detector



Auto Fan Speed



Backlit Remote

App Wifi




Smart Life
Smart Living



Gear Control




Sleep Mode



Dust Filter



Hot/Cold



Golden Fin



R410A Refrigerant



Economy Mode



LED Display